

SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-403-862-3340 (24 Hrs)

Product Name: Liqui-Cover HD / Hydroshield HD Prepared by: Fusion Technologies Inc.

Date Issued: October 19, 2016 # & Version: 140-1.3

1. PRODUCT IDENTIFICATION AND COMPANY IDENTIFICATION

Product Name: Liqui-Cover HD / Hydroshield HD

Product Purpose: Reduction of evaporation from water bodies, pits or tanks

Supplier Identification: BarCliff Energy Services Ltd.

214 Sierra Vista Bay

Calgary, AB T3H 3B8

PREPARER'S TELEPHONE NUMBER: 1 - 587 - 353 - 2940

2. HAZARDS IDENTIFICATION

Hazard Pictograms:



Signal word: Warning

Primary Routes of Exposure: Eyes, and skin

Hazards not otherwise classified (HNOC) or not covered by GHS – none

Acute Effects: Eye: May cause irritation. With prolonged contact, eye tissue injury

and permanent eye damage may occur.

Skin: May cause irritation with prolonged contact.

Ingestion: Not a likely route of exposure. No adverse effect expected.

Inhalation: Repeated or prolonged exposure may irritate the

respiratory tract.

BarCliff Energy Services Ltd. 1 - 403 - 862 - 3340

Page 1 of 7



SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-403-862-3340 (24 Hrs)

Product Name: Liqui-Cover HD / Hydroshield HD Prepared by: Fusion Technologies Inc.

Date Issued: October 19, 2016 # & Version: 140-1.3

Chronic: No adverse effect expected other than those mentioned above.

3. PRODUCT COMPOSITION/INGREDIENTS

Chemical Name CAS # % by Weight

This product is not regulated. None of the substances in this product are hazardous.

4. FIRST AID MEASURES

Eye Contact: Rinse eyes immediately with copious amounts of water and under the

eyelids for at least 20 minutes. In the event that only one eye

contaminated, ensure the uncontaminated eye is not affected by water

run-off. If symptoms persist seek medical advice.

Skin Contact: Remove contaminated clothing. Immediately wash off all chemicals

with soap and copious amounts of water. Remove all contaminated

clothing and footwear under running water.

Ingestion: Do not induce vomiting without medical advice. If conscious,

washout mouth and give person water to drink. Seek medical advice.

Inhalation: Remove to fresh air, treat symptomatically. If symptoms persist, seek

medical advice.

5. FIRE FIGHTING MEASURES

Flash Point: 116 °C (240 °F)
Lower explosion Limit (LEL): Not available
Upper explosion Limit (UEL): Not available
Auto ignition temperature: Not available

Suitable Extinguishing Media: Water spray, foam, CO₂, dry chemical

Fire and explosion Hazard: Not flammable or combustible under normal conditions

BarCliff Energy Services Ltd. 1 - 403 - 862 - 3340



SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-403-862-3340 (24 Hrs)

Product Name: Liqui-Cover HD / Hydroshield HD Prepared by: Fusion Technologies Inc.

Date Issued: October 19, 2016 # & Version: 140-1.3

Specific Methods: Cool tanks and containers with water spray.

Keep product and empty containers away from heat and ignition

Wear self-contained breathing apparatus for fire fighting if required.

sources.

Special Protective Equipment

For Firefighters:

Specific Hazards: Non-combustible. Heating can release hazardous gases.



6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin, eyes and clothing. Evacuate personnel to safe

areas. Keep people away from and upwind of spill or leak. Ventilate

spill area if possible. PPE: see section 8.

Environmental Precautions: N/A

Methods For Cleaning Up: Absorb any spill with an inert material such as sand or earth, and then

place into an appropriate waste container. Remove soiled refuse and

place in a suitable disposal container.

Dispose of material in compliance with local, provincial and

Federal regulations. See Section 13.

7. HANDLING AND STORAGE

Handling Precautions: Handle wearing appropriate PPE as per section 8. Ensure adequate

ventilation is available

Storage Precautions: Store in suitable labeled containers. Store according to Provincial and

Federal regulations. Keep in a dry place.

BarCliff Energy Services Ltd. 1 - 403 - 862 - 3340

Page 3 of 7



SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-403-862-3340 (24 Hrs)

Product Name: Liqui-Cover HD / Hydroshield HD Prepared by: Fusion Technologies Inc.

Date Issued: October 19, 2016 # & Version: 140-1.3

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Occupational Exposure Limits: This product does not contain any substance that has an established

exposure limit.

General ventilation is recommended. Local Exhaust fan may be Engineering Measures:

necessary when dust or mist is generated.

CAS	Chemical Name	ACGIH*
Not applicable	Not applicable	Not applicable

Hygiene Recommendations: Keep an eye wash fountain and safety shower available

Eve Protection: Wear safety glasses with side shields

Hand Protection: Wear Neoprene or Nitrile or PVC or Rubber or Butyl or Cloth

gloves.

Respiratory protection is not normally needed. If respiratory Respiratory Protection:

protection is required, institute a complete respiratory program

including selection, fit testing, training, maintenance and inspections

in accordance with Provincial and Federal regulations.

Wear standard protective clothing – consider to select type of Skin and Body Protection:

protective clothing depending on quantity of chemical to be handled.

*ACGIH – Occupational exposure limits – TWA

PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid Color: Blue to violet

Odor: Slight medicinal like

Boiling Point: Not determined Vapor Pressure: Not applicable Vapor Density: Not determined Relative Density: 0.86 g/mL Not applicable рН: Not soluble in water Solubility: Evaporation Rate: Not applicable

BarCliff Energy Services Ltd. 1 - 403 - 862 - 3340



SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-403-862-3340 (24 Hrs)

Product Name: Liqui-Cover HD / Hydroshield HD

& Version: 140-1.3

Prepared by: Fusion Technologies Inc.

Date Issued: October 19, 2016

Flash Point: 116 °C

Freezing Point: -29 °C (-20.2°F) Viscosity: Not determined

10. STABILITY AND REACTIVITY

Stable under normal conditions

Conditions to Avoid: None

Materials to Avoid: Strong oxidizers Hazardous Polymerization: Will not occur

Hazardous Decomposition Fumes produced when heated may include oxides of carbon

Products:

Under Fire Conditions: Heating can release hazardous gases.

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity:

LD50/oral/rat: 2.9 g/mg

LC50/inhlalation/8hr/rat: No data available

Sensitization: Not expected to be a sensitizer

Mutagenic Effects:No data availableReproductive Toxicity:No data availableCarcinogenic Effects:No data available

Teratogenicity and Embryo No quantitative data available

Toxicity:

Human Experience: Ingestion may cause gastrointestinal irritation, nausea, vomiting,

and diarrhea.

Other Toxicity Information: Toxicological Synergistic products: none known.



SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-403-862-3340 (24 Hrs)

Product Name: Liqui-Cover HD / Hydroshield HD Prepared by: Fusion Technologies Inc.

Date Issued: October 19, 2016 # & Version: 140-1.3

12. ECOLOGICAL INFORMATION

Acute Toxicity:	Fathead Minnow (% survival)	Ceriodaphnia Dubia (% survival)
48 Hour/Static testing:	100	90

^{*}Testing performed by Environmental Toxicity Control Inc. (Minnesota) on February 9, 2015.

13. DISPOSAL INFORMATION

Waste Residues/Unused Product and Package

Dispose of waste in an approved incinerator or waste treatment site, in accordance with all applicable regulations. Do not dispose of wastes in local sewer or with normal garbage.

14. TRANSPORT INFORMATION

Typical proper shipping name for this product are as follows:

PRODUCT IS NOT REGULATED DURING TRANSPORTATION

Important Note: This information does not take the place of shipping paper (Bill of Lading or BOL)

15. REGULATORY INFORMATION

CANADA: Workplace Hazardous Material Information System (WHMIS)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and is not a WHMIS controlled product.

This section contains additional information that may have relevance to regulatory compliance. The information contained in this section is for reference only. BarCliff Energy Services Ltd. accepts no liability for the use of this information.



SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-403-862-3340 (24 Hrs)

Product Name: Liqui-Cover HD / Hydroshield HD Prepared by: Fusion Technologies Inc.

Date Issued: October 19, 2016 # & Version: 140-1.3

16. OTHER INFORMATION

NFPA 704M RATING

Health: 0 Flammability: 0 Instability: 0 Other: n/a

HMIS

Health: 0 Flammability: 0 Instability: 0 Other: n/a 0= insignificant 1= slight 2= moderate 3= high 4= Extreme *= Chronic Hazard

This material safety data sheet provides health and safety information for the safe use of this product provided it is used as recommended per the associated product literature. Users of this product should be aware of the recommended safety precautions. For any other use, exposures must be evaluated so that appropriate handling and training programs can be created and implemented to insure safe workplace operations. Consult with BarCliff Energy Services Ltd. for any additional information.